

FAP40T

4" In-Ceiling Speaker System

Drop Tile Ceiling Installation:

1. Remove the 2' x 2' or 2' x 4' tile.
2. Align the tile bridge on the rear of the tile in the desired position.
3. Using the template provided mark the cutout circle with a marker and cut a 6 $\frac{5}{16}$ " (160.3mm) hole.
4. Replace tile into grid.
5. Bring service loop from rear of the tile, through the tile bridge to the access panel located on the side of the Enclosure. Terminate the service loop to the barrier block connection provided. (Red dot = "+" please note polarity). A $\frac{7}{8}$ " through hole is provided to facilitate conduit. A UL recognized conduit connector should be used to terminate conduit. Connection cavity is not intended for use as a junction box.
6. Insert the enclosure through the front of the tile. Using a standard #2 Phillips screwdriver or screw-gun tighten the three dog leg assemblies until they engage the tile bridge assembly.
DO NOT OVER TIGHTEN DOG LEG SCREWS!
7. Adjust the front mounted switch to the desired tap setting.
NOTE: An 8 Ω setting is included on the selector switch which bypasses the internal transformer for applications where the FAP40T is to be directly coupled to 8 Ω amplifiers.
8. Install the press-fit grille into the front bezel ring. Push the baffle upwards until the baffle is flush with the bezel ring.
9. For safety and seismic considerations, a suspension ring is integrated into the input panel section of the unit. Atlas Sound strongly suggests that a support wire be installed from this support point to a suitable anchor point above the ceiling grid. In drop tile applications, this wire can usually be installed from an adjacent tile access near the speaker location.

Existing Construction Dry Wall ("Hard Deck") Installation

1. Using the template provided mark the cutout circle in the desired mounting location and cut a 6 $\frac{5}{16}$ " (160.3mm) hole.
2. Bring service loop from through the hole to the access panel located on the side of the enclosure. Terminate the service loop to the barrier block connection provided (Red dot = "+" please note polarity). A $\frac{7}{8}$ " through hole is provided to facilitate conduit. A UL recognized conduit connector should be used to terminate conduit. Connection cavity is not intended for use as a junction box.
3. Insert the enclosure into hole. Using a standard #2 Phillips screwdriver or screw-gun tighten the three dog leg assemblies until they engage the tile bridge assembly.
DO NOT OVER TIGHTEN DOG LEG SCREWS!
4. Adjust the front mounted switch to the desired setting.
NOTE: A 8 Ω setting is included on the selector switch which bypasses the internal transformer for applications where the FAP40 is to be directly coupled to 8 Ω amplifiers.

5. Install the press-fit grille into the front bezel ring. Push the baffle upwards until the baffle is flush with the bezel ring.

New Construction (Drywall Ceilings)

Use of the optional FA-TR4 new construction bracket essentially reserves the speaker mounting location prior to drywall installation in new construction. The bracket mounts between 16" or 24" OC studs and includes a $\frac{3}{8}$ " downward lip to provide a template for the drywall installers to cut around. For final installation please follow the instructions below.

Note: The tile bridge is not to be used in new construction applications where the new construction bracket is utilized.

1. Bring service loop from through the hole in ceiling provided by the pre construction bracket to the access panel located on the side of the Enclosure. Terminate the service loop to the barrier block connection provided (Red dot = "+" please note polarity). A $\frac{7}{8}$ " through hole is provided to facilitate conduit. A UL recognized conduit connector should be used to terminate conduit. Connection cavity is not intended for use as a junction box.
2. Insert the speaker assembly into hole. Using a standard #2 Phillips screwdriver or screw-gun tighten the three dog leg assemblies until they engage the ring provided on the new construction bracket.
DO NOT OVER TIGHTEN DOG LEG SCREWS!
3. Adjust the front mounted switch to the desired tap setting.
NOTE: An 8 Ω setting is included on the selector switch which bypasses the internal transformer for applications where the FAP40 is to be directly coupled to 8 Ω amplifiers.
4. Install the press-fit grille into the front bezel ring. Push the baffle upwards until the baffle is flush with the bezel ring.

NOTE:

- Dog legs will accommodate ceiling material thickness up to 1 $\frac{1}{4}$ " as shipped from the factory.
- For thicker ceiling materials (up to 2") simply unscrew and flip the doglegs.
- **DO NOT OVER TIGHTEN DOG LEGS IN ANY CONFIGURATION!**
- ***DO NOT USE 8 Ω SETTING WITH 70.7V/100V SYSTEMS!**
- ***DO NOT OVERPOWER IN 8 Ω CONFIGURATION!**
- **AMPLIFIER OUTPUT SHOULD NOT EXCEED 16 WATTS RMS @ 8 Ω PER SPEAKER**
- A UL recognized conduit clamp must be used for conduit connections.
- Cable connection cavity is not intended to be used as a junction box.
- FA-TR4 not tested or evaluated by Underwriters Laboratories (UL)


Specifications

Frequency Response	120Hz – 15kHz
Sensitivity	86dB (1W / 1M)

FAP40T



4" In-Ceiling Speaker System

Typical Parallel Hookup of Full Range 70.7V / 100V Speakers



Tap Selector Switch Position

Amp Output	1	2	3	4	5	6
70.7V	1 watt	2 watts	4 watts	8 watts	16 watts	Bypass (8Ω)
100V	2 watts	4 watts	8 watts	16 watts	N/A	Bypass (8Ω)



©2011 Atlas Sound L.P. All rights reserved. Atlas Sound is a trademark of Atlas Sound L.P. All other trademarks are the property of their respective owners. All specs are subject to change without notice. ATS001629 Rev.G 7/13