

SM12PS

12" Two-way Full Range Speaker System



Features

- Two-way passive speaker system
- Rotatable horn
- Unique cabinet design
- Water-based paint for environmental purpose

Applications

Near-field portable or installed PA for clubs, theaters and broadcast etc; Fill-in system in conjunction with large TurboPower sound systems; House of worship

General Description

The SM12PS is a versatile, two-way passive system, designed to provide exceptional sound reinforcement and stage monitoring from a very compact enclosure. It features a powerful 12" low frequency driver and a 1" exit HF horn loaded dome tweeter mounted on a constant directivity 80° x 50° horn. The HF horn can be rotated to allow the multi-angle enclosure to be used in either its vertical or horizontal orientation. Multiple internal rigging points for ground-support, truss and wall mounting. Pole mount socket, flush handle and Speakon NL4 connectors.





Specifications Specification	
Frequency Response	60Hz-20kHz±3dB,-10dB@55Hz
Drivers	1 x 12 " LF driver, 1 x 1" exit HF horn loaded dome tweeter
Rated Power (RMS)	400W
Peak Power	1600W
Sensitivity (1W/1m)	98db
Maximum SPL	124dB (continuous), 130dB (peak)
Normal Impedance	8 ohms
Dispersion (-6dB)	80° (Horizontal), 50°(Vertical)
Crossover	2kHz Passive
Finish	Textured black paint
Protective Grille	Black perforated steel
Connectors	2 x Neutrik speakon NL4
Fittings	Top Hat fitting
Dimensions (W x H x D)	356 x 542 x 365 mm
Weight	21Kg