

Description

The 1581NA and 1542NA are compact power amplifier modules capable of driving small loudspeaker loads in a GLOBALCOM system.

The 1581NA provides a single output with 8 watts of power into an 8Ω load. The 1542NA provides two outputs, each with 4 watts of power into an 8Ω load. This makes the module ideal for powering small zones that are made up of only a few low-powered loudspeakers.

The audio inputs to the module are through the Ethernet audio network and are configured from the GLOBALCOM System Management Center. Different models are available that allow the use of either the CobraNet[®] or Dante[®] audio networking protocols.

Both models are powered using standard PoE and draw a maximum power of 13 watts. If PoE equipment is not used, an input is provided for an external +48VDC power supply. A green power indicator LED is included to show that the unit is powered on. Each channel has a green LED indicator that illuminates when signal is present and a yellow LED to indicate clipping. Another yellow LED illuminates to indicate that the device is in thermal overload. When this condition occurs, the device will stop passing signal until the condition has cleared.

The amplifier is provided in an enclosure that either mounts to a DIN rail or is screwed down on a panel or wall to allow for convenient installation in remote closets close to the loudspeaker zone.

Available Models

Model	Channels	Output Power (per channel)	Input Type
1581NA-C	1	8W	CobraNet
1542NA-C	2	4W	CobraNet
1581NA-D	1	8W	Dante
1542NA-D	2	4W	Dante

Features

- Available in single-channel or two-channel configurations
- Available with either CobraNet[®] or Dante[®] audio network interface
- Control and configure using a web browser and GLOBALCOM System Management Center
- Settings storage in non-volatile memory
- Full integration with the IED GLOBALCOM vACS
- Utilizes IEEE 802.af Power over Ethernet (PoE)
- Removable connectors for easy installation
- Rugged DIN-rail or panel/wall mount enclosure

Specifications

Electrical

Power Output

1581NA-C*, 1581NA-D ($R_L = 8 \Omega$) 8 Watts

1542NA-C*, 1542NA-D ($R_L = 8 \Omega$) 4 W/ch

Efficiency

Power Output = 100% 75%

Nominal Loudspeaker Impedance 8Ω

Frequency Response 25 Hz – 15 kHz, –3 dB

Power Bandwidth (+0 dB, –5 dB) 20 Hz – 20 kHz

Signal-to-Noise Ratio (Unweighted, 20 Hz – 20 kHz) > 75 dB

THD + Noise ($P_o = 100\%$ rated output) < 0.05% @ 1 kHz

Power Requirements

Voltage (primary) +48 VDC (PoE)

PoE Power Factor < 13 Watts

External DC Supply Voltage (not included) +48VDC

Indicators

Module Power 1 (Green)

Thermal Overload 1 (Yellow)

Signal Present (each channel) 1 (Green)

Signal Clipping (each channel) 1 (Yellow)

Connectors

Outputs 2-pin Phoenix, 5.08 mm spacing

Network RJ-45

Secondary Power 3-pin Phoenix, 3.81 mm spacing

Mechanical

Height 7.01" (17.81 cm)

Width 3.50" (8.90 cm)

Depth 2.00" (5.28 cm)


Weight 10.0 oz (284 g)

Environmental

Operating Temperature Range –22 °F – +149 °F (–30 °C – +65 °C)

** Due to the PoE maximum power limitation of 13 W, the 1581NA-C and 1542NA-C are limited to a maximum output power of 6.5 W and 3.25 W/ch when powered using PoE. Full output power is available when the module receives its power from an external 48VDC power supply of sufficient wattage.*

Product Dimensions (Front)



Product Dimensions (Side)

