




DT6

6" x 2' Drop Tile Speaker Package



DT6

Features

- All In One, Pre-Assembled Unit Drops Into Ceiling Grids to Reduce Installation Time and Costs
- Solid White Panel with Punched Speaker Grille Blends in with Most Acoustic Ceiling Tiles
- Standard 3" Speaker with Built-In 25V / 70.7V Transformer
- UL1480 / UL2043

Application

Installer friendly Atlas Sound DT6 provides clear paging and background music in a labor saving package. Ideal for use in shopping malls, department stores, and anywhere large quantities of loudspeakers are to be utilized.

General Description

The Atlas Sound DT6 6" x 2' drop in speaker system simplifies loudspeaker installation by providing an all in one speaker package for use in acoustic ceiling grids. The system includes the speaker / transformer, enclosure, and grille. Enjoy clear, crisp paging and background music from the installation friendly DT6 without compromising building cosmetics.

Specifications


Frequency Response	125Hz - 8kHz (± 6dB)
Dispersion	135°- 2kHz Octave Band (-6dB)
Sensitivity (1W/1m)	87dB
Speaker	3" Cone Type
Magnet Weight	5oz (141g)
Length	23.9" (607mm)
Width	5.97" (151.6mm)
Depth	4.2" (106.7mm)
Weight	4.2lbs (1.9 kg)
Color	White

Architect and Engineer Specifications

The loudspeaker, transformer, baffle and enclosure shall be the Atlas Sound 6" x 2' drop in speaker system Model DT6. The loudspeaker shall be a 3" cone type with an integral 25V / 70.7V matching transformer. Power taps to include .25, .5, 1, 2, & 4 Watt for 25V and 70.7V systems. The assembly to include a speaker enclosure mounted to a 6" x 2' white metal panel.

©2014 Atlas Sound L.P. All rights reserved. Atlas Sound and Strategy Series are trademarks of Atlas Sound L.P. All other trademarks are the property of their respective owners. ATS004927 RevA 7/14

DT6 Frequency Response



DT6 Impedance

